



ECO

Duraklick

Flat roof Mounting-System ECO

Duraklick

A brand of SOLTOP Energie GmbH

approved by
German Institute
for Building
Technologies

With the Duraklick-Eco 10°, 15° and 20° system, we offer a particularly economical and inexpensive alternative to our SR system. This flat roof mounting system consists of the same high-quality components as our proven SR system - but without side spoilers and without rear wind plates.

It is manufactured in a lightweight aluminium construction, is self-supporting and is installed without roof penetration. However, compared to the aerodynamically outstanding SR system, it requires a higher ballasting. For higher buildings and/or wind loads, we recommend the use of optional wind plates in the northern area. The wide floor rails and additional building protection mats as a mounting base offer optimum protection for the roof cladding.

**soltop
energie**

Easy to
assemble

Non-roof-
penetrating

Best load
distribution

For more information, please visit www.soltop-energie.ch & www.soltop-energie.eu

SOLTOP Energie AG
St. Gallerstrasse 3
CH-8353 Elgg
info@soltop-energie.ch



SOLTOP Energie GmbH
Lindauer Straße 15
D-88145 Hergatz
info@soltop-energie.eu

SOLTOP Energie SA
Rue des Sablons 8
CH-3960 Sierre
info.fr@soltop-energie.ch

SOLTOP Energie SA
Avenue Haldimand 41
CH-1400 Yverdon-les-Bains
info@soltop-energie.ch

Flat roof Mounting-System ECO

02.2026



Convincing Features:


- Available in three different inclination angles
- Cost-effective and easy to assemble
- Best load distribution due to 230 mm wide floor profile
- High-quality aluminium and stainless steel
- Approved by the German Institute of Building Technologies
Nr. Z 14.4-691
- Compatible with the certified, non-roof-penetrating fall protection system Duraklick HSS
- Made in Germany

The Duraklick-Eco is available in three versions:

ECO 10°

Step size 1,60 m to flexible

Module width 1134 / 30 mm




Technical specifications

Inclination	~10°
Rail length	0,7 - 6,0 m
Modul width	1.040 - 1.210 mm
Surface load	ca. 10,7 kg/m ² *
Line load	ca. 18,1 kg/m *
Material aluminium / stainless steel	
* assuming a module weight of 19 kg and a step size of 1,6 m	

ECO 15°

Step size 1,80 m to flexible

Module width 1134 / 30 mm




Technical specifications

Inclination	~15°
Rail length	0,7 - 6,0 m
Modul width	1.040 - 1.210 mm
Surface load	ca. 9,3 kg/m ² *
Line load	ca. 12,5 kg/m *
Material aluminium / stainless steel	
* assuming a module weight of 19 kg and a step size of 1,8 m	

ECO 20°

Step size 2,00 m to flexible

Module width 1134 / 30 mm



Technical specifications

Inclination	~20°
Rail length	0,7 - 6,0 m
Modul width	1.040 - 1.210 mm
Surface load	ab ca. 7,0 kg/m ² *
Line load	ca. 16,8 kg/m *
Material aluminium / stainless steel	
* assuming a module weight of 19 kg and a step size of 2,0 m	

For more information, please visit www.soltop-energie.ch & www.soltop-energie.eu

SOLTOP Energie AG
St. Gallerstrasse 3
CH-8353 Elgg
info@soltop-energie.ch

SOLTOP Energie GmbH
Lindauer Straße 15
D-88145 Hergatz
info@soltop-energie.eu

SOLTOP Energie SA
Rue des Sablons 8
CH-3960 Sierre
info.fr@soltop-energie.ch

SOLTOP Energie SA
Avenue Haldimand 41
CH-1400 Yverdon-les-Bains
info@soltop-energie.ch